TX32T-H


High reliable, temperature compensated
LVCMOS TCXO

QuartzCom
the communications company

Preliminary specification

Frequency range	**10.000 ~ 60.000 MHz**		
Frequency stability:			
vs. temperature referenced to (FMAX+FMIN)/2	≤ ±2.5 ppm	over -40 to +85 °C	(∗)
vs. supply voltage changes referenced to frequency at nominal supply	≤ ±0.2 ppm	±5 %	
vs. load changes referenced to frequency at nominal load	≤ ±0.1 ppm	±5 %	
vs. aging @ +40 °C	≤ ±1.0 ppm	1st year	
G-sensitivity	< 2.0 ppb/g	per axis	
Frequency tolerance ex. factory	≤ ±2.0 ppm	@ +25 °C	
Supply voltage	+1.8 V, +2.5 V, +3.0 V or +3.3 V		(∗)
Output signal	(LV)CMOS		
Output level	V_{OH} > 0.9∗Vcc / V_{OL} < 0.1∗Vcc		
Output load	15 pF Max.		
Current consumption, depending on frequency	10 mA Max.		
Tri-state function	pin # 1 ≥ 70% Vcc or NC pin # 1 ≤ 30% Vcc or GND	pin # 3 ➔ signal pin # 3 ➔ high impedance	
Phase noise (typical value for 40 MHz)	-85 dBc/Hz -115 dBc/Hz -135 dBc/Hz -150 dBc/Hz -155 dBc/Hz	@ 10 Hz @ 100 Hz @ 1 kHz @ 10 kHz @ 100 kHz	
Operating temperature range	-40 ~ +85 °C		(∗)
Storage temperature range	-55 ~ +105 °C		
Reflow Profiles as per IPC/JEDEC J-STD-020C	≤ 260 °C over 10 sec. Max.		
Moisture sensitivity	Level 1 (unlimited)		


(∗) See available options on page #2 **Note: Unless otherwise specified conditions are @+25 °C**




Pin function

# 1	ED or NC
# 2	GND
# 3	Output
# 4	Vcc

Soldering pattern



Test circuit for CMOS



2011/65/EU RoHS compliant

QuartzCom AG
Bruehlstrasse 15
CH 2540 Grenchen
Switzerland

Fax +41 32 644 24 05
Tel +41 32 644 24 00
E-Mail sales@quartzcom.com
www.quartzcom.com

Designed in Switzerland

QuartzCom AG reserves the right to make spec changes to this product

TX32T-H

High reliable, temperature compensated
LVCMOS TCXO

QuartzCom
the communications company

Preliminary specification

Ordering code

TX5T-(1)(2)-(3)(4)-20.000MHz *Example:* ***TX5T-H33-NM5u0-20.000MHz***

Oscillator type	**(1) Output signal**	**(2) Supply voltage**	**(3) Operating temperature**
TX = TCXO	H = (LV)CMOS	18 = 1.8 V 25 = 2.5 V 30 = 3.0 V 33 = 3.3 V	NN = -40 to +85 °C NM = -40 to +90 °C NR = -40 to +105 °C
			(4) Frequency stability 2u5 = ± 2.5 ppm 5u0 = ± 5.0 ppm 10u0 = ± 10.0 ppm

Frequency stability vs. temperature

ppm	≤± 2.5	≤± 5.0	≤± 10.0
-40 to +85 °C	Δ	O	O
-40 to +90 °C	Δ	Δ	O
-40 to +105 °C	O	Δ	O

Δ Ask factory
O Available
X Not available

Environmental conditions

Test	**IEC 60068 Part…**	**IEC 60679-1 Clause**	**MIL-STD-202G Method**	**MIL-STD-810F Method**	**MIL-PRF-55310D Clause**	**Test conditions (IEC)**
Sealing tests (if applicable)	2-17	5.6.2	112E		3.6.1.2	Gross leak: Test Qc, Fine leak: Test Qk
Solderability Resistance to soldering heat	2-20 2-58	5.6.3	208H 210F		3.6.52 3.6.48	Test Ta method 1, Test Td_1 method 2, Test Td_2 method 2
Shock *	2-27	5.6.8	213B	516.4	3.6.40	Test Ea, 3 x per axis 100 g, 6 ms half-sine pulse
Vibration, sinusoidal*	2-6	5.6.7.1	201A 204D	516.4-4	3.6.38.1 3.6.38.2	Test Fc, 30 min per axis, 1 oct/min 10 Hz – 55 Hz 0,75 mm; 55 Hz – 2 kHz, 10 g
Vibration, random*	2-64	5.6.7.3	214A	514.5	3.6.38.3 3.6.38.4	Test Fdb
Endurance tests - ageing - extended ageing		 5.7.1 5.7.2	108A		4.8.35	 30 days @ 85 °C 1000 h, 2000 h, 8000 h @ 85 °C

Other environmental conditions on request

QuartzCom AG
Bruehlstrasse 15
CH 2540 Grenchen
Switzerland

Fax +41 32 644 24 05
Tel +41 32 644 24 00
E-Mail sales@quartzcom.com
www.quartzcom.com

Designed in Switzerland

QuartzCom AG reserves the right to make spec changes to this product

Handling Recommendation for SMD Crystal & Crystal Oscillator

1. ESD Handling

Crystal oscillators are electrostatic sensitive device. Therefore, direct touching of the terminals with fingers and without ESD precautions must be avoid.
Proper handling must be made according to the established ESD handling rules IEC 61340-5-1 and EN 100015-1 to avoid degradations of the oscillator performance due to damages of the internal circuitry by electrostatic discharge.

2. Shocks & Vibrations


Excessive mechanical shocks and or vibrations during handling as well as manual and automatic assembly must be avoided.
If accidently, the component was dropped or subject to strong shock, component should be verified that the electrical function is still within the specification and still hermetically sealed.

3. Thermal Shocks

Avoid steep temperature gradients. It might lead to breakage of the crystal blank
Infrared reflow processes in general are safe.

4. Soldering & Cleaning

Maximum Reflow Condition in accordance with JEDEC STD-020C



Avoid washing or welding processes using Ultrasonic energy. These processes can damage the crystal due to mechanical resonance of the crystal blanks.

5. Coating

Using resin may have an impact on the oscillator characteristics.
If resin is used, please contact QuartzCom or our representative for more information.
In situations where resin would be used without contacting us in advance,
QuartzCom will not be responsible for any damages caused to the components or and injuries caused to people.

QuartzCom AG
Bruehlstrasse 15
CH 2540 Grenchen
Switzerland

Fax +41 32 644 24 05
Tel +41 32 644 24 00
E-Mail sales@quartzcom.com
www.quartzcom.com

Designed in Switzerland

QuartzCom AG reserves the right to make spec changes to this product